Accessories






Disc Diffuser



Rubber Saddles

JetFlex® Disc Diffusers with R¾" nipple may be installed onto all plastic pipes suitable for waste water and hot air. Grommets are suitable for all plastic pipes with outer diameter between 89 and 141 mm (3½ and 59/16 inch). Wall thickness for the Universal Saddle should be between 4 and 8 mm (5/32 and 5/16 inch). The exertion force for this saddle is approximately 850 N with discs properly installed. Universal Saddles work with all JetFlex® disc diffuser with ¾" male thread. For further details please refer to our Technical Information "Installation (of JetFlex® Disc Diffusers) using EPDM-Grommets" at www.jaeqer-envirotech.com



part-no.	description	material	colour
01005199	rubber saddle universal	EPDM	black

PVC Saddles

PVC Saddles are made from U-PVC and may be glued onto 90 and 110 mm PVC pipes (U-PVC and/or C-PVC). They are equipped with a $G\frac{34}{7}$ female thread. The opening in the header pipe should measure 36 ± 0.5 mm. You may rectify slight deviations in diameter and position of bore by accurately positioning the saddle on top of the pipe, thread pointing exactly upwards. For detailed information on gluing the saddle to the header please refer to instructions from glue manufacturers, e.g. Tangit by Henkel at www.tangit.com or equivalent. You may have to secure the position of the clamp by cable ties or similar means for 5 minutes or more depending on temperature.



part-no.	description	material	colour
02003662	saddle 90 mm	PVC	white
02004508	saddle 90 mm	PVC	grey
02003663	saddle 110 mm	PVC	white
02004509	saddle 110 mm	PVC	grey

Check Valve (for JetFlex® HD200, HD270 and HD340 with R¾ external thread)

Check valves (non-return-valves) consist of a PP housing containing an 8 mm SS-ball. The stainless-steel ball prevents backflow of sludge into headers in case of damage to the membrane of the disc. Check valves alter the headloss characteristic of JetFlex® disc diffusers, so do not install discs with and without check valve in the same tank or on the same grid. Check valves work best if discs are installed using our clamp adaptors 90 N or our rubber saddles, see above.



part-no.	description	material	colour
02003636	non-return valve	PPC30%GF/SS	white



Disc- / Tube Diffuser

Clamp Adapters

Clamp adapters come in a variety of sizes and threads. They require a 40 +0 -1 mm hole in the header pipe. For disc diffusers this hole must point exactly upwards. Short tube diffusers (max. 560 mm length) have to be leveled within ± 5 mm at the ends, so both 40 mm holes must be aligned horizontally. Tube diffusers longer than 560 mm should be fixed using our fixing plates and L-brackets mentioned on page 6. All clamps come with a cable-tie-like mounting aid freeing your hands during installation. Clamps are installed in pairs. You need two threaded ones (1" male) for a pair of tubes or one threaded and one blind one for a single tube. Discs require one threaded and one blind clamp. Clamp adapters 90N have been designed especially for 90 mm headers with existing openings of about 15 mm. You may connect any JetFlex® disc diffuser with a set of one 90N-clamp R¾ and one blind clamp. This threaded clamp easily accommodates our check-valve giving you full compatibility, if necessary. Clamp adapter 90N-G1 male thread may be used to connect tube diffusers onto 90 mm plastic headers. The clamp requires a 16 mm opening in the header (+1/-0 mm). This clamp causes some additional headloss for airflow rates above 8 m³/h per diffuser. Nuts, bolts and washers are within the scope of supply. O-Ring is included with all threaded clamps.

Clamp Adapters with male thread

ı	part-no.	description	material	colour
	02003754	clamp adapter 114.3 with 1" male thread	PP20%GF/SI/SS	black
	02003902	clamp adapter 110 with 1" male thread	PP20%GF/SI/SS	black
	02004699	clamp adapter 90 N with 1" male thread	PP20%GF/SI/SS	black



Clamp Adapters with female thread

part-no.	description	material	colour
02003756	clamp adapter 114.3 with R ¾ female thread	PP20%GF/SI/SS	black
02003904	clamp adapter 110 with R ¾ female thread	PP20%GF/SI/SS	black
02003977	clamp adapter 90 N with R ¾ female thread	PP20%GF/SI/SS	black



Clamp Adapters without thread

part-no.	description	material	colour
02003755	clamp adapter 114.3 without thread	PP20%GF/SS	black
02003903	clamp adapter 110 without thread	PP20%GF/SS	black
02003978	clamp adapter 90 N without thread	PP20%GF/SS	black





Adapters

Existing diffusers on square tubes may be mounted using different connectors and openings. We carry adapters for existing openings of 40 and 45 mm. There is no need for an additional gasket. The existing connectors are replaced by our 1" stainless-steel connectors, see further below.



part-no.	description	material	colour
02003669	Flange Seal 40 mm	Desmopan	white
02004874	Flange Seal 45 mm	Desmopan	white

¹ As a matter of principle each carton with tube diffusers contains the appropriate amount of EPDM or silicone gaskets. In combination with Desmopan-Adapters you do not need these gaskets.

Stainless-steel clamps

Replacing sleeves requires new clamps to secure sleeves on support tubes. We do not recommend the use of worm-gear-clamps as these clamps may squeeze and crimp the sleeve. This may damage the sleeve or cause air-leakage at the clamp. See our installation instructions for details. V2A clamps (SS304) are stocked, V4A clamps (SS316) are available, too, but non-stock items.



part-no.	description	material
12000601	clamp 66.5 mm diameter	V2A
12000602	clamp 68.0 mm diameter	V2A
12000603	clamp 69.5 mm diameter	V2A
12000761	clamp 95.0 mm diameter	V2A

Pincer

This pincer is ideally suited to close above mentioned stainless-steel clamps. A regular pair of pliers may deform the ear of the clamp and is regarded as an emergency repair tool only.



part-no.	description
91002831	pincer

Sealing for Tube Diffusers JetFlex® TD65-2 G

Tube diffusers usually include all necessary sealing. If for any reason diffusers are disassembled we strongly recommend replacing the seals upon re-installation.



part-no.	description	material	colour
06018329	gasket TD65-2 G1	Silicone	red
06031688	gasket TD65-2 ¾	Silicone	red



Tube Diffuser

Sealing for Tube Diffusers JetFlex® TD63-0 (formerly TD 63/2 - - -)

Tube diffusers usually include all necessary sealing. If for any reason diffusers are disassembled we strongly recommend replacing the seals upon re-installation.



part-no.	description	material	colour
06017160	gasket 63x27x4 mm	EPDM	black
06017161	gasket 63x34x4 mm	EPDM	black
06017163	gasket 63x27x4 mm	Silicone	red
06017164	gasket 63x34x4 mm	Silicone	red

Blind Plugs

Many tube diffusers in Europe are installed onto square-tube-headers. Occasionally there is the need to omit individual diffusers due to obstructions in the tank etc. Blind plugs allow you to install a single diffuser either side of the header. Of course, a pair of diffusers may be replaced by a pair of blind plugs, too. Diffusers with ¾" NPT usually are not installed in pairs, so the applicable blind plug serves as a cap or plug to shut off unused existing connections.



part-no.	description	material	colour
02003667	blind plug G¾"	PP30%GF	green
02003668	blind plug G1"	PP30%GF	blue
02003670	blind plug ¾" NPT	PP30%GF	grey

Stainless-Steel Connectors (Square headers)

For almost all kinds of square and rectangular pipes there is a connector for our tube diffusers. Other lengths are available on request.



part-no.	description	material
21000601	connector ¾", length 130 mm	V2A
21000602	connector ¾", length 150 mm	V2A
21001848	connector 1", length 130 mm	V2A
21001847	connector 1", length 150 mm	V2A
21001846	connector 1", length 170 mm	V2A
21001853	connector ¾", length 145 mm	V2A
21001851	connector ¾", length 165 mm	V2A
21001854	connector 1", length 145 mm	V2A
21001850	connector 1", length 165 mm	V2A
21001844	connector 1", length 185 mm	V2A

Tube Diffuser



Plastic connectors / Saddles (Round headers)

In order to join tube diffusers intended for square headers to 4-inch round headers there is a special connecting set available. Each set consists of 2 saddles and one connector threaded on both ends with 1" male threads



part-no.	description	material	colour
01005958	saddle for 4" pipes	PP30%GF/EPDM	black
02003713	connector for 4" pipes	PA6 GF25	black

Fixing Plates

Tube diffusers may be exposed to high water currents near blade mixers etc. This may cause oscillatory instability particularly with regard to long diffusers. In order to avoid flapping of diffusers this special end cap may be inserted into the far end of the tube and fixed to the ground. The end cap does not hamper water flowing into the open end of the diffuser keeping the buoyancy of the tube low. Please specify installation height of diffusers in order to select the proper length of the SS brackets.



part-no.	description	material	colour	threaded nut
02003661	fixing plate for TD63	PP	green	M10
02004797	fixing plate for TD65	PP	black	M8

L-brackets

part-no.	description	material	threaded nut
21999999	bolt, washer, L-bracket (please call)	SS	M8/M10



Pipe Support

Pipe supports are made from stainless steel (ANSI 304/316) with adjustable height for laterals and headers in order to achieve optimum uniformity of aeration. Available sizes are for 4"and 6" laterals and headers as well as for DN100 and DN150 metric sizes. Please, call for details.



description	material
pipe support 110/114.3/160 mm	SS



GENERAL SALES CONDITIONS LÄGER LIMMELT-TECHNIK GMBH

- Unions extension agence, our prisons on to inconducate of the SUREA and shall great for decision?.

 Our last of purific great plans WAT. The cartainties will be made on the break of the pulses being with the conduction.
- I m giver be consistent paint on stall justice the pulsar equality of all contributions the translations on the last pulsar stalled by a Pile Right whole the formation of the pulsar stalled by a Pile Right whole the first pulsar of the pulsar of the

- 1. Payment and on-off.
 1. Our involves because due with 14 departure dails of limites in detaching 2 and discount or with 15 days let. In any case the present from in the limite has to be unto wealth to us of the best on-thick and in the present of the limite has to linguish because the best hosted by the office of the limited present in the limited present in the limited by the detaching to consider the restrict.
 1. Invoice instructs below 60.00 BUR (film) and there for waaring, repairs, wealth and present information belong considering.
 2. Constructions belong considering to so heling of no legal time do not easily the linguishment to real next in all present in the linguishment appeal upon, but it the being from others, we are collect to broke all appeals to the present appeal upon. But it the being from others, we are collect to broke all appeals to the many of the actual present all but in the accept of the character of the character of the property of the actual time actually detached by a detaching actually administration of the character of the c
- details removed.

 In the condition or dates, enterspeed to the conduction of the conduct, our anticipant become of one-particular or the part of the large, we shall be entitled to make use of the lattle of the part of the part of the lattle of the conduction of the lattle of the la

- Coloury have and shall are explained as submodels when up to its analytic subject of delivery has inflored having. Coloury dates and the americal to a measurable establishment of allow and habitude as well with gape of a formation is produced unity gapes in a recording on a large and appropriate produced produced and the product of the delivery of the manifestors considered. This shall state upply the produced produced by the produced produced by the produced produced by the produced produced by the produced

- jet, wheel country. The present of a principle is continued a provide the principle in the country. The present of a principle is the first flow provides a country of the principle is the country of the principle is the principle is the principle is the principle is the principle in the principle is the principle in the principle in the principle is the principle in the principle in the principle is the principle in the princip that he go plant compared on he has beginned on the property and the second of the sec
- of pays justices requires and or has as he is not be realised being on that the
- construction with all between the recording to program the process, the fit is not recorded to process the process to record the program of the process of the record process to the program of the record process to the record of th

- If the word but have been the eighty records consistent countries of the state of t

- Performance of defination
 Affice these street the mandation in functed over to the forestate, but at the interferent the people projecting our residence of the people over the forestate people over the forest th
- tenerable persymbol. In deliveril and we registed to it.

 If the many the deliver.

 In case of a bundle, prospirentes of deliver many to our deliver regist to deliver and registered persons.

 In case of a bundle, prospired persons Packer Charge, Would the electrons of deliver a registered person of the control of the

- erranse etc. The Deprengraly date deliction goods. The alternative conduct variables of the delictional houston according to the condition of the project of the condition of the deliction factors with the condition of the project VIII. This expectify applies to chief deprengration of the condition of the condition for (designs asset by a del
- The state of the s
- These indulars and not part in our of extent others update country contents to the least of the country of the
- A transplant of the second process of the se
- Chipman.
 We have be properly high and equity if on all other, drain, that
 with may pay by dynamic to a thin party men our causest. Dans
 halo particles also have to benchman to begin myses.
- In the count hat the deligned entitled to extend to be desired to entitle politically of the deligned entitled to the larger from the larger than the factor that posterior against of the property of the country of each object to the production and deligned of each object to the production of the productio
- the This being at the Theory and in the Holl. At his part of the part of the Theory has
- Regard to the country to the series of the conjugate which we receive the few products of series products to had series to the series for all series for all series to the series to had series to the series for all series to the series

- Using electric speed it, our total offer shall be to place of performance for our defication. If classic speed is, our total offer shall be to place of performance for our defication. If classic speed is related to the performance of the per

- is case of dealt, for German worker of Saran Germani Camillians of Portions and apply

Promise No. 9,740 M.C.



Jäger Umwelt-Technik GmbH

Lohweg 1 30559 Hannover Germany

୬ +49 511 646 440

+49 511 646 444 99

www.jaeger-envirotech.com



Disclaimer

We exclude any liability for the information and product presentations provided. Contents of technical character are based on the date of publication. Existing copyrights and rights to the use of names remain unaffected.