

JetFlex® CBD 105 Coarse Bubble Diffuser



★ NHẬP KHẨU VÀ CUNG CẤP ★
CÔNG TY
TRÁCH NHIỆM HỮU HẠN
XÂY DỰNG VÀ
THƯƠNG MẠI
QUANG MINH
★ TRADING AND SUPPLY ★
★ CÔNG TY TNHH LÝ THƯỜNG KIỆT VÀ HỢP CẤP ★



Membrane material

Silicone

Diffuser body

Reinforced Polypropylene (PP-GF) with R ¾" external tapered thread

Dimensions

Overall Diameter	Total Height	Threaded Length	Membrane Thickness
105 mm	45 mm	25 mm	2 mm

Installation

You may install CBD 105 using our rubber saddle (EPDM) or our plastic saddle clamp. Please see our brochure "Accessories" for details and further alternatives.



Performance data

Airflow	Headloss	SSOTE
Minimum: 2 m³/h (33 liters/minute) @ STP	10 hPa	2 %/m
Maximum: 25 m³/h (420 liters/minute) @ STP	40 hPa	1 %/m

Coarse bubble diffusers are mainly used through mixing capabilities. The rising air induces a strong current, thus removing sludge from the bottom of the tank. They are therefore a very good alternative for many mechanical aeration systems.



Jäger Umwelt-Technik GmbH
 Ruscheplattenstraße 14
 31137 Hildesheim
 Germany
 ☎ +49 5121 9138 900
 📠 +49 5121 9138 999
 www.jaeger-envirotech.com
 info@jaeger-envirotech.com



Disclaimer

We exclude any liability for the information and product presentations provided. Contents of technical character are based on the date of publication. Existing copyrights and rights to the use of names remain unaffected.

